

Articulated Dumper Range



D 100 A



D 120 A



D 150 A



D 300 A



D 350 A



D 450 A



D 601 A



DR 601 A



D 1001 A



DR 1001 A



| AUSA | Weight (lb) | Capacity (cu yd) | Water | hp | Wheelbase (in) | Wheelbase (in) | Wheelbase (in) | Wheelbase (in) | Weight (lb) | Attachment |
|---------------------|-------------|------------------|-------|------|----------------|----------------|----------------|----------------|-------------|------------|
| D 100 AHA / COMPACT | 2,200 | 0.74 | 0.45 | 20.9 | 37.4/35.8 | 126.0 | 43.3/39.4 | 94.5/92.9 | 2,866 | H-4x4 |
| D 100 AHG | 2,200 | 0.71 | 0.42 | 20.9 | 37.4 | 126.0 | 43.3 | 94.5 | 2,866 | H-4x4 |
| D 120 AHA | 2,600 | 0.91 | 0.55 | 20.9 | 39.0 | 126.0 | 47.6 | 96.1 | 3,031 | H-4x4 |
| D 120 AHG | 2,600 | 0.90 | 0.54 | 20.9 | 39.4 | 126.0 | 47.6 | 96.1 | 3,031 | H-4x4 |
| D 150 AHA | 3,300 | 1.10 | 0.79 | 20.9 | 39.0 | 126.0 | 58.3 | 96.1 | 3,329 | H-4x4 |
| D 150 AHG | 3,300 | 1.18 | 0.68 | 20.9 | 39.4 | 129.9 | 58.3 | 96.1 | 3,329 | H-4x4 |
| D 300 AHG | 6,600 | 2.74 | 0.94 | 24.8 | 37.0 | 159.1 | 72.4 | 109.1 | 5,954 | H-4x4 |
| D 350 AHG | 7,700 | 2.78 | 1.33 | 44 | 34.3 | 164.2 | 72.8 | 109.1 | 6,241 | H-4x4 |
| D 450 AHG | 9,900 | 3.49 | 1.79 | 44 | 28.9 | 172.4 | 73.6 | 111.0 | 6,548 | H-4x4 |
| D 601 AHG | 13,200 | 4.12 | 2.18 | 74.3 | 48.0 | 193.3 | 87.0 | 129.1 | 9,898 | H-4x4 |
| D 601 AP | 13,200 | 4.16 | 2.47 | 74.3 | 16.5 | 183.9 | 87.0 | 129.1 | 9,900 | P-4x4 |
| D 601 APG | 13,200 | 4.12 | 2.18 | 74.3 | 48.0 | 193.3 | 87.0 | 129.1 | 10,353 | P-4x4 |
| 2021 DR 601 AHG | 13,200 | 4.12 | 2.18 | 74.3 | 48.0 | 193.3 | 87.0 | 142.1 | 10,648 | H-4x4 |
| D 1001 APG | 22,000 | 5.10 | 2.42 | 74.3 | 49.6 | 197.6 | 94.9 | 143.3 | 11,431 | P-4x4 |
| 2021 DR 1001 AHG | 22,000 | 5.10 | 2.42 | 74.3 | 49.6 | 197.6 | 94.9 | 143.3 | 11,133 | H-4x4 |

Rigid Dumper Range



D 201 R



| AUSA | Weight (lb) | Capacity (cu yd) | Water | hp | Wheelbase (in) | Wheelbase (in) | Wheelbase (in) | Wheelbase (in) | Weight (lb) | Attachment |
|------------|-------------|------------------|-------|------|----------------|----------------|----------------|----------------|-------------|------------|
| D 201 RHS | 4,400 | 1.63 | 0.91 | 24.8 | 22.4 | 118.9 | 68.9 | 101.6 | 4,188 | H-4x4 |
| D 201 RHGS | 4,400 | 1.61 | 0.85 | 24.8 | 36.6 | 129.1 | 68.9 | 101.6 | 4,630 | H-4x4 |



Sound Heavy Machinery
 1809 Blue Clay Road
 Wilmington, NC 28405
 (910) 782-2477
www.SoundHM.com
info@SoundHM.com

AUSA US CORP
 9481 Industrial Center Dr, Unit 3,
 Ladson, SC 29456
 TEL: (843) 202 0387
ausa.us@ausa.com

AUSA Center: +34 93 874 7311 - ausa@ausa.com
 AUSA Spain: +34 91 669 00 06 ausa.madrid@ausa.com
 AUSA France: +33 (0) 4 68 54 38 97 - ausa.france@ausa.fr
 AUSA U.K.: +44 (0)7703 60 9009 - ausa.uk@ausa.com
 AUSA Central Europe: +49 2384 9415725 - info@ausa.de
 AUSA Brasil: +55 11 40146906 - ausa.brasil@ausa.com
 AUSA CHINA: +86 10 8598 7386 - ausa.china@ausa.com



MKCAT.TR.US.03



www.ausa.com

Forklift Range



| AUSA | lb* | lb** | ft | hp | in | in | in | in | in | in | lb | |
|-----------|-------|--------|-------|------|-------|------|------|-------|-----|--------|-------|--|
| C 150 H | 3,300 | 3,000 | 8.73 | 24.8 | 142.9 | 51.2 | 78.7 | 80.2 | 25% | 5,950 | H-4x2 | |
| C 150 Hx4 | 3,300 | 3,000 | 8.73 | 24.8 | 142.9 | 51.2 | 80.3 | 80.2 | 25% | 5,950 | H-4x4 | |
| C 201 H | 4,400 | 4,000 | 10.82 | 24.8 | 172.4 | 51.2 | 82.3 | 94.9 | 25% | 8,170 | H-4x2 | |
| C 201 Hx4 | 4,400 | 4,000 | 10.82 | 24.8 | 172.4 | 51.2 | 82.3 | 94.9 | 40% | 7,650 | H-4x4 | |
| C 251 H | 5,500 | 5,000 | 10.82 | 41.8 | 172.6 | 59.8 | 84.2 | 96.8 | 25% | 9,149 | H-4x2 | |
| C 251 Hx4 | 5,500 | 5,000 | 10.82 | 41.8 | 172.6 | 59.8 | 84.6 | 96.8 | 38% | 9,414 | H-4x4 | |
| C 351 Hx4 | 7,700 | 7,000 | 10.82 | 41.8 | 178.4 | 70.1 | 86.2 | 105.1 | 30% | 11,940 | H-4x4 | |
| C 400 Hx4 | - | 8,800 | 12.14 | 74.2 | 181.9 | 78.2 | 91.7 | 108.2 | 35% | 16,314 | H-4x4 | |
| C 500 Hx4 | - | 11,000 | 12.14 | 74.2 | 181.9 | 78.2 | 91.7 | 108.2 | 35% | 17,010 | H-4x4 | |

* Load Capacity to 20" ** Load Capacity to 24"

Telehandler Range



| AUSA | lb | ft | in | hp | in | in | in | in | in | lb | |
|---------|-------|------|-------|------|-----|-------|------|------|--------|---------|--|
| T 144 H | 3,000 | 13.1 | 66.22 | 24.8 | 25% | 145.1 | 55.3 | 78.7 | 5,290 | H-4x4 | |
| T 204 H | 4,400 | 13.8 | 81.57 | 42.9 | 42% | 186.2 | 62.6 | 79.9 | 9,149 | H-4x4x4 | |
| T 235 H | 5,000 | 16.4 | 92.83 | 42.9 | 44% | 192.1 | 62.6 | 79.8 | 10,250 | H-4x4x4 | |



The most complete range
of compact machinery